



6022LLUC3/EM Bearing 2D drawings and 3D CAD models

NTN 6022LLUC3/EM Single Row Ball Bearings

Bearing No. 6022LLUC3/EM

Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight	1.98
EAN	4547359551105
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C3-Loose
Inch - Metric	Metric
Long Description	110MM Bore; 170MM Outside Diameter; 28MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68



Xiamen Senhengyuan Machinery Equipmen...

Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	6022LLUC3/5C
Weight / LBS	4.32
Outer Race Width	1.102 Inch 28 Millimeter
d	4.331 Inch 110 Millimeter
D	6.693 Inch 170 Millimeter
bore diameter:	110 mm
precision rating:	ISO Class 0
outside diameter:	170 mm
finish/coating:	Uncoated
overall width:	28 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	28 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	28 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	2300 rpm
internal clearance:	C3
fillet radius:	2 mm
operating temperature range:	-40 to 120 ° C
maximum rpm:	4500 RPM
dynamic load capacity:	82000 N
series:	60
static load capacity:	73000 N
manufacturer product page:	Click here